C&Lube Co., Ltd. since 1995
tel.82-52-239-5189 fax.82-52-239-5105

Special Lubricants

Custom Made Oils & Greases

182, Hwasan-ro, Onsan-up, UlJu-kun, Ulsan, KOREA 45009

www.cnlube.co.kr, e-mail : adm@cnlube.co.kr

Certification of Analysis

Customer **INDIVIDUAL ENTREPRENUER** **D a t e 30-Jan-26**

Product **Black Eagle Diesel Semi-Synthetic 10W40 API CG-4 (TBN:12.57)** **Lot. No. 26012932**

Test Item	Test Method	Spec.	Results
Appearance	Visual	Clear & Bright	C & B
Density(15℃), kg/㎥	ASTM D 287	Report	867,8
Kinematic Viscosity (100℃), ㎟/s	ASTM D 445	12.5 ~ 16.3	14,46
Viscosity Index	ASTM D 2270	85 min.	150
Apparent Viscosity (-25℃), Pa.S	ASTM D 5293	7.0 max.	5,25
Flash Point, ℃	ASTM D 92	195 min.	232
Pour Point, ℃	ASTM D 97	-24 max.	-39
Total Base Number, ㎎KOH/g	ASTM D 2896	-	12,67

This data is for your reference and it can't be used for any legal purpose.

Research & Development Center

Manager J. S. KIM