



www.cnlube.co.kr

TEL 82-52-239-5189 FAX 82-52-239-5105

New Technology Resources

Special Lubricants Oil & Grease

182, Hwasan-ro, Onsan-eup, Ulju-gun, Ulsan, KOREA 45009

e-mail : adm@cnlube.co.kr

Certification Of Analysis

Customer	INDIVIDUAL ENTREPRENUER	D a t e	27-Oct-22
Product	EAGLE SCORPION Gear Oil API GL-4 80W90	Lot. No.	22102625

Test Item	Test Method	Spec.	Results
Appearance	Visual	Clear Brown Fluid	Clear Brown Fluid
Density (15°C), kg/m ³	ASTM D 287	Report	886.3
Kinematic Viscosity, mm ² /s, (100°C)	ASTM D 445	13.5-24	16.08
Viscosity Index	ASTM D 2270	Min. 85	107
Flash Point (°C)	ASTM D 92	Min. 180	244
Pour Point, (°C)	ASTM D 97	Max. -21	-24
Copper corrosion (100°C, 3h)	ASTM D 130	1 max.	1b
Foaming Characteristics, ml	Sequence I	ASTM D 892	20/0
	Sequence II		50/0
	Sequence III		20/0

This data is for your reference and it can't be used for any legal purpose.

Research & Development Center

Manager J. H. Lee

