C&Lube Co., Ltd. since 1995
tel.82-52-239-5189 fax.82-52-239-5105

Special Lubricants

Custom Made Oils & Greases

182, Hwasan-ro, Onsan-up, UlJu-kun, Ulsan, KOREA 45009

www.cnlube.co.kr, e-mail : adm@cnlube.co.kr

Certification of Analysis

Customer **INDIVIDUAL ENTREPRENUER** **D a t e 4-Jul-25**

Product **Black Eagle Diesel Semi Synthetic 15W40 API CG-4 (TBN 12.57)** **Lot. No. 25063026**

Test Item	Test Method	Spec.	Results
Appearance	Visual	Clear & Bright	C & B
Density(15℃), kg/㎥	ASTM D 287	Report	871,5
Kinematic Viscosity (100℃), ㎟/s	ASTM D 445	12.5 ~ 16.3	15,04
Viscosity Index	ASTM D 2270	85 min.	141
Apparent Viscosity (-20℃), Pa.S	ASTM D 5293	7.0 max.	4,10
Flash Point, ℃	ASTM D 92	195 min.	232
Pour Point, ℃	ASTM D 97	-24 max.	-36
Total Base Number, ㎎KOH/g	ASTM D 2896	Report	12,75

This data is for your reference and it can't be used for any legal purpose.

Research & Development Center

Manager J. S. KIM