



C&Lube Co., Ltd. since 1995
tel.82-52-239-5189 fax.82-52-239-5105

Special Lubricants
Custom Made Oils & Greases

182, Hwasan-ro, Onsan-up, UIJu-kun, Ulsan, KOREA, 45009
www.cnlube.co.kr, e-mail : adm@cnlube.co.kr

Certification of Analysis

Customer INDIVIDUAL ENTREPRENUER **Date** 25-Aug-22
Product EAGLE Gasoline Semi-Synthetic 10W40 API SL **Lot. No.** 22082221

Test Item		Test Method	Spec.	Results
Appearance		Visual	Clear & Bright	C & B
Density(15°C), kg/m ³		ASTM D 287	Report	855.5
Kinematic Viscosity(100°C), mm ² /s		ASTM D 445	12.5 ~ 16.3	14.72
Viscosity Index		ASTM D 2270	85 min.	157
Low Temperature Cranking Viscosity(-25 °C), Pa·s		ASTM D 5293	7.0 max.	4.45
Flash Point, °C		ASTM D 92	195 min.	224
Pour Point, °C		ASTM D 97	-24 max.	-39
Oxidation Stability (165.5°C, 24hr)	Viscosity Change Ratio	JIS K 2514	1.5 max.	1.00
	TAN Change ,mgKOH/g		1.6 max.	0.45
	Lacquer		Thin	Nil

This data is for your reference and it can't be used for any legal purpose.

Research & Development Center

Manager J. H. Lee

