



C&Lube Co., Ltd. since 1995
tel.82-52-239-5189 fax.82-52-239-5105

Special Lubricants
Custom Made Oils & Greases

182, Hwasan-ro, Onsan-up, UIJu-kun, Ulsan, KOREA 689-896
www.cnlube.co.kr, e-mail : adm@cnlube.co.kr

Certification of Analysis

Customer	INDIVIDUAL ENTREPRENUER	Date	26-Aug-22
Product	Eagle Gasoline Semi-Synthetic 10W30 API SL	Lot. No.	22082523

Test Item	Test Method	Spec.	Results	
Appearance	Visual	Clear & Bright	C & B	
Density((15°C), kg/m³)	ASTM D 287	Report	859.2	
Kinematic Viscosity(100°C), mm²/s	ASTM D 445	9.3 ~ 12.5	10.72	
Viscosity Index	ASTM D 2270	85 min.	144	
Low Temperature Cranking Viscosity(-25 °C), Pa·s	ASTM D 5293	7.0 max.	4.35	
Flash Point, °C	ASTM D 92	190 min.	228	
Pour Point, °C	ASTM D 97	-24 max.	-39	
Oxidation Stability (165.5°C, 24hr)	Viscosity Change Ratio	JIS K 2514	1.5 max.	0.99
	TAN Change ,mgKOH/g		1.6 max.	0.45
	Lacquer		Thin	Nil

This data is for your reference and it can't be used for any legal purpose.

Research & Development Center

Manager J. H. Lee

