



C&Lube Co., Ltd. since 1995
tel.82-52-239-5189 fax.82-52-239-5105

Special Lubricants
Custom Made Oils & Greases

182, Hwasan-ro, Onsan-up, UIJu-kun, Ulsan, KOREA 689-896
www.cnlube.co.kr, e-mail : adm@cnlube.co.kr

Certification of Analysis

Customer **INDIVIDUAL ENTREPRENUER**
Product **EAGLE HD SAE 30 API CF-4**

Date **11-Mar-21**
Lot. No. **21031022**

Test Item		Test Method	Spec.	Results
Appearance		Visual	Clear & Bright	C & B
Density((15°C), kg/m ³)		ASTM D 287	Report	879.6
Kinematic Viscosity(100°C), mm ² /s		ASTM D 445	9.3 ~ 12.5	9.786
Viscosity Index		ASTM D 2270	85 min.	104
Flash Point, °C		ASTM D 92	190 min.	228
Pour Point, °C		ASTM D 97	-24 max.	-39
Total Base Number, mgKOH/g		ASTM D 2856	Report	12.0
Oxidation Stability (165.5°C, 24hr)	Viscosity Change Ratio	JIS K 2514	1.5 max.	0.98
	TAN Change ,mgKOH/g		1.6 max.	0.40
	Lacquer		Thin	Nil

This data is for your reference and it can't be used for any legal purpose.

Research & Development Center

Manager J. H. Lee

