



C&Lube Co., Ltd. since 1995

tel.82-52-239-5189 fax.82-52-239-5105

Special Lubricants

Custom Made Oils & Greases

182, Hwasan-ro, Onsan-up, UIJu-kun, Ulsan, KOREA, 45009

www.cnlube.co.kr, e-mail : adm@cnlube.co.kr

Certification of Analysis

Customer	INDIVIDUAL ENTREPRENUER	Date	18-Feb-25
Product	EAGLE PAO-D1 SYNTHETIC 10W40 API CK-4 (TBN 12.5)	Lot. No.	25021328

Test Item	Test Method	Spec.	Results
Appearance	Visual	Clear & Bright	C & B
Density(15°C), kg/m ³	ASTM D 287	Report	857,5
Kinematic Viscosity(100°C), mm ² /s	ASTM D 445	12.5 ~ 16.3	14,20
Viscosity Index	ASTM D 2270	85 min.	157
Low Temperature Cranking Viscosity(-25 °C), Pa·s	ASTM D 5293	7.0 max.	4,60
Flash Point, °C	ASTM D 92	195 min.	234
Pour Point, °C	ASTM D 97	-24 max.	-39
Total Base Number, mgKOH/g	ASTM D 2856	Report	13,15

This data is for your reference and it can't be used for any legal purpose.

Research & Development Center

Manager J. S. KIM

