



**C&Lube Co., Ltd. since 1995**

tel.82-52-239-5189 fax.82-52-239-5105

**Special Lubricants**

**Custom Made Oils & Greases**

182, Hwasan-ro, Onsan-up, UIJu-kun, Ulsan, KOREA, 45009

www.cnlube.co.kr, e-mail : adm@cnlube.co.kr

**Certification of Analysis**

<b>Customer</b>	<b>INDIVIDUAL ENTREPRENUER</b>	<b>Date</b>	<b>25-Nov-25</b>
<b>Product</b>	<b>EAGLE PAO D1 Synthetic 5W40 API CK-4 (PAO 10%) (TBN 12.5)</b>	<b>Lot. No.</b>	<b>25112029</b>

Test Item	Test Method	Spec.	Results
Appearance	Visual	Clear & Bright	C & B
Density(15°C), kg/m <sup>3</sup>	ASTM D 287	Report	854,1
Kinematic Viscosity(100°C), mm <sup>2</sup> /s	ASTM D 445	12.5 ~ 16.3	14,14
Viscosity Index	ASTM D 2270	85 min.	175
Low Temperature Cranking Viscosity(-30 °C), Pa·s	ASTM D 5293	6.6 max.	4,80
Flash Point, °C	ASTM D 92	195 min.	226
Pour Point, °C	ASTM D 97	-30 max.	-48
Total Base Number, mgKOH/g	ASTM D 2856	Report	12,55

This data is for your reference and it can't be used for any legal purpose.

**Research & Development Center**

**Manager J. S. KIM**

