



www.cnlube.co.kr

TEL 82-52-239-5189 FAX 82-52-239-5105

New Technology Resources
Special Lubricants Oil & Grease

182, Hwasan-ro, Onsan-eup, Ulju-gun, Ulsan City, KOREA

e-mail : adm@cnlube.co.kr

Certification Of Analysis

Customer **INDIVIDUAL ENTREPRENUER** **Date** **25-Jun-26**
Product **EAGLE PEGASUS MULTI CVT LV** **Lot. No.** **26062531**

Test Item		Test Method	Spec.	Results
Apearance		Visual	Clear Fluid	Clear Fluid
Density (15 °C), kg/m ³		ASTM D 287	Report	846,3
Viscosity (100 °C), mm ² /s		ASTM D 445	Min. 5.5	5,632
Viscosity Index		ASTM D 2270	Min. 120	177
Flash Poiont(C.O.C, °C)		ASTM D 92	Min. 170	196
Pour Point(°C)		ASTM D 97	Max. -39	- 57
Foaming Characteristics (ml)	Sequence I	ASTM D 892	100 / 0	10/0
	Sequence II		100 / 0	20/0
	Sequence III		100 / 0	10/0
Rust Preventive (Distilled Water, 24hr)		ASTM D 665	Pass	Pass

This data is for your reference and it can't be used for any legal purpose.

Research & Development Center

Manager J. S. KIM

