



C&Lube Co., Ltd. since 1995
tel.82-52-239-5189 fax.82-52-239-5105

Special Lubricants
Custom Made Oils & Greases

182, Hwasan-ro, Onsan-up, UIJu-kun, Ulsan, KOREA, 45009
www.cnlube.co.kr, e-mail : adm@cnlube.co.kr

Certification of Analysis

Customer	INDIVIDUAL ENTREPRENUER	D a t e	12-Mar-21
Product	EAGLE PREMIUM Gasoline 100% synthetic 5W40 API SN	Lot. No.	21031026

Test Item	Test Method	Spec.	Results	
Appearance	Visual	Clear & Bright	C & B	
Density(15°C), kg/m ³	ASTM D 287	Report	852.3	
Kinematic Viscosity(100°C), mm ² /s	ASTM D 445	12.5 ~ 16.3	13.92	
Viscosity Index	ASTM D 2270	85 min.	171	
Apparent Viscosity (-30°C), Pa.S	ASTM D 5293	6.6 max.	4.80	
Flash Point, °C	ASTM D 92	195 min.	232	
Pour Point, °C	ASTM D 97	-24 max.	-42	
Oxidation Stability (165.5°C, 24hr)	Viscosity Change Ratio	JIS K 2514	1.5 max.	0.98
	TAN Change ,mgKOH/g		1.6 max.	0.30
	Lacquer		Thin	Nil

This data is for your reference and it can't be used for any legal purpose.

Research & Development Center
Manager J. H. Lee

