



C&Lube Co., Ltd. since 1995  
tel.82-52-239-5189 fax.82-52-239-5105

**Special Lubricants**  
**Custom Made Oils & Greases**

182, Hwasan-ro, Onsan-eup, UIJu-gun, Ulsan, KOREA 45009  
www.cnlube.co.kr, e-mail : adm@cnlube.co.kr

## Certification Of Analysis

**Customer** INDIVIDUAL ENTREPRENUER **Date** 2-Sep-22  
**Product** EAGLE SCORPION Gear Oil API GL-5 75W90 **Lot. No.** 22090124

Test Item	Test Method	Spec.	Results
Appearance	Visual	Clear & Bright	C & B
Density(15°C), kg/m³	ASTM D 287	Report	848.1
Kinematic Viscosity(100°C), mm²/s	ASTM D 445	13.5 ~ 24.0	15.68
Viscosity Index	ASTM D 2270	85 min.	159
Flash Point (Open cup method, °C)	ASTM D 92	180 min.	236
Pour Point, °C	ASTM D 97	-24 max.	-45
Copper Corrosion (100 °C, 3h)	ASTM D 130	1 max	1b
Foaming Characteristics, mℓ	Sequence I	ASTM D 892	20 / 0
	Sequence II	ASTM D 892	50 / 0
	Sequence III	ASTM D 892	20 / 0

This data is for your reference and it can't be used for any legal purpose.

Research & Development Center

Manager J. H. Lee

