



**C&Lube Co., Ltd. since 1995**

tel.82-52-239-5189 fax.82-52-239-5105

**Special Lubricants**

**Custom Made Oils & Greases**

182, Hwasan-ro, Onsan-up, UIJu-kun, Ulsan, KOREA, 45009

www.cnlube.co.kr, e-mail : adm@cnlube.co.kr

## Certification of Analysis

<b>Customer</b>	<b>INDIVIDUAL ENTREPRENUER</b>	<b>Date</b>	<b>28-Jul-25</b>
<b>Product</b>	<b>EAGLE SPEED FE 5W30 SYNTHETIC API SP RC, ACEA C2</b>	<b>Lot. No.</b>	<b>25072823</b>

Test Item	Test Method	Spec.	Results
Appearance	Visual	Clear & Bright	C & B
Density(15°C), kg/m <sup>3</sup>	ASTM D 287	Report	849,7
Kinematic Viscosity(100°C), mm <sup>2</sup> /s	ASTM D 445	9.3 ~ 12.5	10,12
Viscosity Index	ASTM D 2270	85 min.	173
Apparent Viscosity(-30°C), Pa.S	ASTM D 5293	6.6 max.	4,20
Flash Point, °C	ASTM D 92	190 min.	224
Pour Point, °C	ASTM D 97	-30 max.	-42

This data is for your reference and it can't be used for any legal purpose.

**Research & Development Center**

**Manager J. S. KIM**

