



**C&Lube Co., Ltd.** since 1995  
tel.82-52-239-5189 fax.82-52-239-5105

**Special Lubricants**  
**Custom Made Oils & Greases**

182, Hwasan-ro, Onsan-eup, UIJu-gun, Ulsan, KOREA 45009  
www.cnlubeoils.com, e-mail : adm@cnlube.co.kr

## Certification Of Analysis

**Customer**

**Date**

**8-Aug-19**

**Product**

**ATF CVT**

**Lot. No.**

**Typical Data**

Test Item		Test Method	Spec.	Results
Appearance		Visual	Orange Clear Fluid	Red Clear Fluid
Density (15°C), kg/m <sup>3</sup>		ASTM D 287	Report	846.6
Viscosity, 100°C, mm <sup>2</sup> /s		ASTM D 445	Min. 5.5	6.821
Viscosity Index		ASTM D 2270	Min. 90	170
Flash Point(C.O.C, °C)		ASTM D 92	Min. 170	204
Pour Point(°C)		ASTM D 97	Max. -39	- 51
Foaming Characteristics (ml)	Sequence I	ASTM D 892	100 / 0	10/0
	Sequence II		100 / 0	20/0
	Sequence III		100 / 0	10/0
Rust Preventive (Distilled Water, 24hr)		ASTM D 665	Pass	Pass

This data is for your reference and it can't be used for any legal purpose.

**Research & Development Center**

**Manager J. H. Lee**

