



C&Lube Co., Ltd. since 1995
tel.82-52-239-5189 fax.82-52-239-5105

Special Lubricants
Custom Made Oils & Greases

182, Hwasan-ro, Onsan-up, UIJu-kun, Ulsan, KOREA 45009
www.cnlube.co.kr, e-mail : adm@cnlube.co.kr

Certification of Analysis

Customer	INDIVIDUAL ENTREPRENUER	Date	10-Mar-21
Product	Eagle Diesel Mineral 15W40 API CF-4	Lot. No.	21030926

Test Item	Test Method	Spec.	Results
Appearance	Visual	Clear & Bright	C & B
Density(15°C), kg/m ³	ASTM D 287	Report	871.8
Kinematic Viscosity (100°C), mm ² /s	ASTM D 445	12.5 ~ 16.3	14.65
Viscosity Index	ASTM D 2270	85 min.	150
Apparent Viscosity (-20°C), Pa.S	ASTM D 5293	7.0 max.	3.50
Flash Point, °C	ASTM D 92	195 min.	230
Pour Point, °C	ASTM D 97	-24 max.	-39
Total Base Number, mgKOH/g	ASTM D 2896	-	12.2
Oxidation Stability (165.5°C, 24hr)	Viscosity Change Ratio	JIS K 2514	1.5 max.
	TAN Change ,mgKOH/g		1.6 max.
	Lacquer		Thin
			Nil

This data is for your reference and it can't be used for any legal purpose.

Research & Development Center

Manager J. H. Lee

