C&Lube Co., Ltd. since 1995
tel.82-52-239-5189 fax.82-52-239-5105

Special Lubricants
Custom Made Oils & Greases

182, Hwasan-ro, Onsan-up, UlJu-kun, Ulsan, KOREA 689-896
www.cnlube.co.kr, e-mail : adm@cnlube.co.kr

Certification of Analysis

Customer **INDIVIDUAL ENTREPRENUER** **D a t e** **19-Jan-21**
Product **EAGLE Diesel Mineral 10W30 API CF-4** **Lot. No.** **21011822**

Test Item		Test Method	Spec.	Results
Appearance		Visual	Clear & Bright	C & B
Density((15℃), kg/㎥		ASTM D 287	Report	869.8
Kinematic Viscosity(100℃), ㎟/s		ASTM D 445	9.3 ~ 12.5	10.28
Viscosity Index		ASTM D 2270	85 min.	132
Low Temperature Cranking Viscosity(-25 ℃), Pa·s		ASTM D 5293	7.0 max.	5.45
Flash Point, ℃		ASTM D 92	190 min.	232
Pour Point, ℃		ASTM D 97	-24 max.	-39
Total Base Number, mgKOH/g		ASTM D 2856	-	12.3
Oxidation Stability (165.5℃, 24hr)	Viscosity Change Ratio	JIS K 2514	1.5 max.	0.98
	TAN Change ,㎎KOH/g		1.6 max.	0.42
	Lacquer		Thin	Nil

This data is for your reference and it can't be used for any legal purpose.

Research & Development Center
Manager J. H. Lee