



C&Lube Co., Ltd. since 1995
tel.82-52-239-5189 fax.82-52-239-5105

Special Lubricants
Custom Made Oils & Greases

311, Hwasan, Onsan, Ul-Ju, Ulsan, Korea
www.cnlube.co.kr, e-mail : adm@cnlube.co.kr

PRODUCT DATA SHEET

Name : C&L Outboard 2T TC-W3

DESCRIPTION

C&L Outboard 2T TC-W3 is formulated for high performance, water cooled two stroke motor oil used in outboard marine application. C&L Outboard Super keeps engine clean and provides reliable and longlasting engine performance. This oil is prediluted to facilitate mixing when added to fuel.

CHARACTERISTICS

- Deposit control by excellent thermal and oxidation stability
- Excellent corrosion protection
- Longer engine life by outstanding anti-wear protection
- Reliable operation in wide range of temperature
- Helps cleaner combustion
- No toxicity to marine life

APPLICATION

- Water cooled, two stroke outboard engines
- Applicable where API-TC, JASO FB, NMMA TC-W, TC-WII and TC-W are recommended
- Useable for engines made by Johnson, Yamaha, Mercruiser, Mercury, Mariner, Suzuki....

TYPICAL TEST RESULT

| | | |
|----------------------------------|-------|---------------|
| Appearance | | Clear and Red |
| Density g/cm ³ (15°C) | | N/A |
| Kinematic Viscosity (cSt) | 40°C | 52.8 |
| | 100°C | 8.8 |
| Sulfate Ash (Wt%) | | N/A |
| Flash Point, °C | | 114 |
| Pour Point, °C | | -36 |